

LK9 105 HHS (radio) 200mm LED 105x105cm folding frame

TECHNICAL FEATURES

Description

LK9 warning cross, 105 x 105 cm, with 9 amber Ø200 mm LED lamps (EN 12352 L8H, 2200 cd) on an electric folding frame for roof mounting.

EN 12352
Class L8H

BEK 393/2025
Compliant (DK)

RS485
Canbus control

OPTICAL FEATURES

Light source

9 x Ø200 mm amber LED lamps, 72 LEDs each

EN 12352 class

L8H

Luminous intensity

2200 cd per lamp

Display modes

Cross, corner lamps

Flash cycle

1.5 s period, 0.6 s lit

Dimming

Photosensor-driven, 5-level automatic

ELECTRICAL FEATURES

Supply voltage

12 V (24 V via external converter kit)

Lamp current

0.89 A per lamp

Average power consumption

approx. 3.2 A / 38 W (daylight, 12 V, lamps only)

Control

RS485 canbus, back-lit operator panel

Remote control

Prepared for radio remote (2+4 or 3x5 radio transmitter, sold separately)

MECHANICAL FEATURES

Panel size

1050 x 1050 mm

Mounting

Electric horizontal folding frame for roof or roof-rack mounting

Housing

Matte-black aluminium with stainless-steel frame

Weight

approx. 34 kg

