

# LK9 105 LHS (cable) 200mm LED 105x105cm vertical lift

## TECHNICAL FEATURES

|                                                                                                                                               |  |                                                                               |  |                                |  |
|-----------------------------------------------------------------------------------------------------------------------------------------------|--|-------------------------------------------------------------------------------|--|--------------------------------|--|
| Description                                                                                                                                   |  | EN 12352<br>Class L8H                                                         |  | BEK 393/2025<br>Compliant (DK) |  |
| LK9 warning cross, 105 x 105 cm, with 9 amber Ø200 mm LED lamps (EN 12352 L8H, 2200 cd) on an electric vertical lift for pickup-bed mounting. |  | RS485<br>Canbus control                                                       |  |                                |  |
| OPTICAL FEATURES                                                                                                                              |  |                                                                               |  |                                |  |
| Light source                                                                                                                                  |  | 9 x Ø200 mm amber LED lamps, 72 LEDs each                                     |  |                                |  |
| EN 12352 class                                                                                                                                |  | L8H                                                                           |  |                                |  |
| Luminous intensity                                                                                                                            |  | 2200 cd per lamp                                                              |  |                                |  |
| Display modes                                                                                                                                 |  | Cross, corner lamps                                                           |  |                                |  |
| Flash cycle                                                                                                                                   |  | 1.5 s period, 0.6 s lit                                                       |  |                                |  |
| Dimming                                                                                                                                       |  | Photosensor-driven, 5-level automatic                                         |  |                                |  |
| ELECTRICAL FEATURES                                                                                                                           |  |                                                                               |  |                                |  |
| Supply voltage                                                                                                                                |  | 12 V (24 V via external converter kit)                                        |  |                                |  |
| Lamp current                                                                                                                                  |  | 0.89 A per lamp                                                               |  |                                |  |
| Average power consumption                                                                                                                     |  | approx. 3.2 A / 38 W (daylight, 12 V, lamps only)                             |  |                                |  |
| Control                                                                                                                                       |  | RS485 canbus, back-lit operator panel                                         |  |                                |  |
| Remote control                                                                                                                                |  | Prepared for cable remote (2+4 or 3x5 cable hand controller, sold separately) |  |                                |  |
| MECHANICAL FEATURES                                                                                                                           |  |                                                                               |  |                                |  |
| Panel size                                                                                                                                    |  | 1050 x 1050 mm                                                                |  |                                |  |
| Mounting                                                                                                                                      |  | Electric vertical lift for pickup-bed mounting behind the driver cab          |  |                                |  |
| Housing                                                                                                                                       |  | Matte-black aluminium with stainless-steel frame                              |  |                                |  |
| Weight                                                                                                                                        |  | approx. 36 kg                                                                 |  |                                |  |

