

LK9 105 LHS (radio) 200mm LED 105x105cm vertical lift

TECHNICAL FEATURES

Description		EN 12352 Class L8H	BEK 393/2025 Compliant (DK)
LK9 warning cross, 105 x 105 cm, with 9 amber Ø200 mm LED lamps (EN 12352 L8H, 2200 cd) on an electric vertical lift for pickup-bed mounting.		RS485 Canbus control	
OPTICAL FEATURES			
Light source	9 x Ø200 mm amber LED lamps, 72 LEDs each		
EN 12352 class	L8H		
Luminous intensity	2200 cd per lamp		
Display modes	Cross, corner lamps		
Flash cycle	1.5 s period, 0.6 s lit		
Dimming	Photosensor-driven, 5-level automatic		
ELECTRICAL FEATURES			
Supply voltage	12 V (24 V via external converter kit)		
Lamp current	0.89 A per lamp		
Average power consumption	approx. 3.2 A / 38 W (daylight, 12 V, lamps only)		
Control	RS485 canbus, back-lit operator panel		
Remote control	Prepared for radio remote (2+4 or 3x5 radio transmitter, sold separately)		
MECHANICAL FEATURES			
Panel size	1050 x 1050 mm		
Mounting	Electric vertical lift for pickup-bed mounting behind the driver cab		
Housing	Matte-black aluminium with stainless-steel frame		
Weight	approx. 36 kg		

