

LK9 105 PM (radio) 200mm LED 105x105cm surface mount

TECHNICAL FEATURES

Description		EN 12352 Class L8H		BEK 393/2025 Compliant (DK)	
LK9 warning cross, 105 x 105 cm, with 9 amber Ø200 mm LED lamps (EN 12352 L8H, 2200 cd) on a fixed surface mount.		RS485 Canbus control			
OPTICAL FEATURES					
Light source		9 x Ø200 mm amber LED lamps, 72 LEDs each			
EN 12352 class		L8H			
Luminous intensity		2200 cd per lamp			
Display modes		Cross, corner lamps			
Flash cycle		1.5 s period, 0.6 s lit			
Dimming		Photosensor-driven, 5-level automatic			
ELECTRICAL FEATURES					
Supply voltage		12 V (24 V via external converter kit)			
Lamp current		0.89 A per lamp			
Average power consumption		approx. 3.2 A / 38 W (daylight, 12 V, lamps only)			
Control		RS485 canbus, back-lit operator panel			
Remote control		Prepared for radio remote (2+4 or 3x5 radio transmitter, sold separately)			
MECHANICAL FEATURES					
Panel size		1050 x 1050 mm			
Mounting		Fixed surface mounting on vehicle body, tailgate, roof rack or hoop frame			
Housing		Matte-black aluminium with stainless-steel frame			
Weight		approx. 22 kg			

