

LK9 80 HHS (cable) 140mm LED 80x80cm folding frame

TECHNICAL FEATURES

Description		EN 12352 Class L2H		BEK 393/2025 Compliant (DK)	
LK9 warning cross, 80 x 80 cm, with 9 amber Ø140 mm LED lamps (EN 12352 L2H, 1500 cd) on an electric folding frame for roof mounting.		RS485 Canbus control			
OPTICAL FEATURES					
Light source		9 x amber LED lamps, Ø140 mm light opening (Ø150 mm housing)			
EN 12352 class		L2H			
Luminous intensity		1500 cd per lamp			
Display modes		Cross, corner lamps			
Flash cycle		1.5 s period, 0.6 s lit			
Dimming		Photosensor-driven, 5-level automatic			
ELECTRICAL FEATURES					
Supply voltage		12 V (24 V via external converter kit)			
Lamp current		0.42 A per lamp			
Average power consumption		approx. 1.5 A / 18 W (daylight, 12 V, lamps only)			
Control		RS485 canbus, back-lit operator panel			
Remote control		Prepared for cable remote (2+4 or 3x5 cable hand controller, sold separately)			
MECHANICAL FEATURES					
Panel size		800 x 800 mm			
Mounting		Electric horizontal folding frame for roof or roof-rack mounting			
Housing		Matte-black aluminium with stainless-steel frame			
Weight		approx. 29 kg			

