

LK9 80 HHS (radio) 140mm LED 80x80cm folding frame

TECHNICAL FEATURES

Description		EN 12352 Class L2H	BEK 393/2025 Compliant (DK)
LK9 warning cross, 80 x 80 cm, with 9 amber Ø140 mm LED lamps (EN 12352 L2H, 1500 cd) on an electric folding frame for roof mounting.		RS485 Canbus control	
OPTICAL FEATURES			
Light source	9 x amber LED lamps, Ø140 mm light opening (Ø150 mm housing)		
EN 12352 class	L2H		
Luminous intensity	1500 cd per lamp		
Display modes	Cross, corner lamps		
Flash cycle	1.5 s period, 0.6 s lit		
Dimming	Photosensor-driven, 5-level automatic		
ELECTRICAL FEATURES			
Supply voltage	12 V (24 V via external converter kit)		
Lamp current	0.42 A per lamp		
Average power consumption	approx. 1.5 A / 18 W (daylight, 12 V, lamps only)		
Control	RS485 canbus, back-lit operator panel		
Remote control	Prepared for radio remote (2+4 or 3x5 radio transmitter, sold separately)		
MECHANICAL FEATURES			
Panel size	800 x 800 mm		
Mounting	Electric horizontal folding frame for roof or roof-rack mounting		
Housing	Matte-black aluminium with stainless-steel frame		
Weight	approx. 29 kg		

