

LK9 80 LHS (cable) 140mm LED 80x80cm vertical lift

TECHNICAL FEATURES

Description	EN 12352 Class L2H	BEK 393/2025 Compliant (DK)
LK9 warning cross, 80 x 80 cm, with 9 amber Ø140 mm LED lamps (EN 12352 L2H, 1500 cd) on an electric vertical lift for pickup-bed mounting.		RS485 Canbus control

OPTICAL FEATURES	
Light source	9 x amber LED lamps, Ø140 mm light opening (Ø150 mm housing)
EN 12352 class	L2H
Luminous intensity	1500 cd per lamp
Display modes	Cross, corner lamps
Flash cycle	1.5 s period, 0.6 s lit
Dimming	Photosensor-driven, 5-level automatic
ELECTRICAL FEATURES	
Supply voltage	12 V (24 V via external converter kit)
Lamp current	0.42 A per lamp
Average power consumption	approx. 1.5 A / 18 W (daylight, 12 V, lamps only)
Control	RS485 canbus, back-lit operator panel
Remote control	Prepared for cable remote (2+4 or 3x5 cable hand controller, sold separately)
MECHANICAL FEATURES	
Panel size	800 x 800 mm
Mounting	Electric vertical lift for pickup-bed mounting behind the driver cab
Housing	Matte-black aluminium with stainless-steel frame
Weight	approx. 31 kg

