

LP15 105 HHS (radio) 200mm LED 105x105cm folding frame

TECHNICAL FEATURES

Description	EN 12352 Class L8H	BEK 393/2025 Compliant (DK)
LP15 warning arrow, 105 x 105 cm, with 15 amber Ø200 mm LED lamps (EN 12352 L8H, 2200 cd) on an electric folding frame for roof mounting.		RS485 Canbus control

OPTICAL FEATURES	
Light source	15 x Ø200 mm amber LED lamps, 72 LEDs each
EN 12352 class	L8H
Luminous intensity	2200 cd per lamp
Display modes	Cross, arrow left, arrow right, corner lamps
Flash cycle	1.5 s period, 0.6 s lit
Dimming	Photosensor-driven, 5-level automatic
ELECTRICAL FEATURES	
Supply voltage	12 V (24 V via external converter kit)
Lamp current	0.89 A per lamp
Average power consumption	approx. 3.2 A / 38 W (daylight, 12 V, max. 9 lamps lit, lamps only)
Control	RS485 canbus, back-lit operator panel
Remote control	Prepared for radio remote (2x4 or 3x5 radio transmitter, sold separately)
MECHANICAL FEATURES	
Panel size	1050 x 1050 mm
Mounting	Electric horizontal folding frame for roof or roof-rack mounting
Housing	Matte-black aluminium with stainless-steel frame
Weight	approx. 36 kg

