

# LP15 105 PM (cable) 200mm LED 105x105cm surface mount

## TECHNICAL FEATURES

| Description                                                                                                         |
|---------------------------------------------------------------------------------------------------------------------|
| LP15 warning arrow, 105 x 105 cm, with 15 amber Ø200 mm LED lamps (EN 12352 L8H, 2200 cd) on a fixed surface mount. |

**EN 12352**  
Class L8H

**BEK 393/2025**  
Compliant (DK)

**RS485**  
Canbus control

## OPTICAL FEATURES

|                    |                                              |
|--------------------|----------------------------------------------|
| Light source       | 15 x Ø200 mm amber LED lamps, 72 LEDs each   |
| EN 12352 class     | L8H                                          |
| Luminous intensity | 2200 cd per lamp                             |
| Display modes      | Cross, arrow left, arrow right, corner lamps |
| Flash cycle        | 1.5 s period, 0.6 s lit                      |
| Dimming            | Photosensor-driven, 5-level automatic        |

## ELECTRICAL FEATURES

|                           |                                                                               |
|---------------------------|-------------------------------------------------------------------------------|
| Supply voltage            | 12 V (24 V via external converter kit)                                        |
| Lamp current              | 0.89 A per lamp                                                               |
| Average power consumption | approx. 3.2 A / 38 W (daylight, 12 V, max. 9 lamps lit, lamps only)           |
| Control                   | RS485 canbus, back-lit operator panel                                         |
| Remote control            | Prepared for cable remote (2x4 or 3x5 cable hand controller, sold separately) |

## MECHANICAL FEATURES

|            |                                                                           |
|------------|---------------------------------------------------------------------------|
| Panel size | 1050 x 1050 mm                                                            |
| Mounting   | Fixed surface mounting on vehicle body, tailgate, roof rack or hoop frame |
| Housing    | Matte-black aluminium with stainless-steel frame                          |
| Weight     | approx. 24 kg                                                             |

