

LP15 80 AHT (radio) 140mm LED 80x80cm hitch mount

TECHNICAL FEATURES

Description

LP15 warning arrow, 80 x 80 cm, with 15 amber Ø140 mm LED lamps (EN 12352 L2H, 1500 cd) on a tow-ball hitch mount.

EN 12352
Class L2H

BEK 393/2025
Compliant (DK)

RS485
Canbus control

OPTICAL FEATURES

Light source

15 x amber LED lamps, Ø140 mm light opening (Ø150 mm housing)

EN 12352 class

L2H

Luminous intensity

1500 cd per lamp

Display modes

Cross, arrow left, arrow right, corner lamps

Flash cycle

1.5 s period, 0.6 s lit

Dimming

Photosensor-driven, 5-level automatic

ELECTRICAL FEATURES

Supply voltage

12 V (24 V via external converter kit)

Lamp current

0.42 A per lamp

Average power consumption

approx. 1.5 A / 18 W (daylight, 12 V, max. 9 lamps lit, lamps only)

Control

RS485 canbus, back-lit operator panel

Remote control

LP15 2x4 radio remote controller included

MECHANICAL FEATURES

Panel size

800 x 800 mm

Mounting

Tow-ball hitch mount, no bodywork modification needed

Housing

Matte-black aluminium with stainless-steel frame

Weight

approx. 33 kg (including hitch mount)

