

LP15 80 HHS (radio) 140mm LED 80x80cm folding frame

TECHNICAL FEATURES

Description

LP15 warning arrow, 80 x 80 cm, with 15 amber Ø140 mm LED lamps (EN 12352 L2H, 1500 cd) on an electric folding frame for roof mounting.

EN 12352
Class L2H

BEK 393/2025
Compliant (DK)

RS485
Canbus control

OPTICAL FEATURES

Light source	15 x amber LED lamps, Ø140 mm light opening (Ø150 mm housing)
EN 12352 class	L2H
Luminous intensity	1500 cd per lamp
Display modes	Cross, arrow left, arrow right, corner lamps
Flash cycle	1.5 s period, 0.6 s lit
Dimming	Photosensor-driven, 5-level automatic

ELECTRICAL FEATURES

Supply voltage	12 V (24 V via external converter kit)
Lamp current	0.42 A per lamp
Average power consumption	approx. 1.5 A / 18 W (daylight, 12 V, max. 9 lamps lit, lamps only)
Control	RS485 canbus, back-lit operator panel
Remote control	Prepared for radio remote (2x4 or 3x5 radio transmitter, sold separately)

MECHANICAL FEATURES

Panel size	800 x 800 mm
Mounting	Electric horizontal folding frame for roof or roof-rack mounting
Housing	Matte-black aluminium with stainless-steel frame
Weight	approx. 31 kg

