

LP15 80 PM (cable) 140mm LED 80x80cm surface mount

TECHNICAL FEATURES

Description

LP15 warning arrow, 80 x 80 cm, with 15 amber Ø140 mm LED lamps (EN 12352 L2H, 1500 cd) on a fixed surface mount.

EN 12352
Class L2H

BEK 393/2025
Compliant (DK)

RS485
Canbus control

OPTICAL FEATURES

Light source	15 x amber LED lamps, Ø140 mm light opening (Ø150 mm housing)
EN 12352 class	L2H
Luminous intensity	1500 cd per lamp
Display modes	Cross, arrow left, arrow right, corner lamps
Flash cycle	1.5 s period, 0.6 s lit
Dimming	Photosensor-driven, 5-level automatic

ELECTRICAL FEATURES

Supply voltage	12 V (24 V via external converter kit)
Lamp current	0.42 A per lamp
Average power consumption	approx. 1.5 A / 18 W (daylight, 12 V, max. 9 lamps lit, lamps only)
Control	RS485 canbus, back-lit operator panel
Remote control	Prepared for cable remote (2x4 or 3x5 cable hand controller, sold separately)

MECHANICAL FEATURES

Panel size	800 x 800 mm
Mounting	Fixed surface mounting on vehicle body, tailgate, roof rack or hoop frame
Housing	Matte-black aluminium with stainless-steel frame
Weight	approx. 20 kg

