

# LP15 80 PM (radio) 140mm LED 80x80cm surface mount

## TECHNICAL FEATURES

Description

LP15 warning arrow, 80 x 80 cm, with 15 amber Ø140 mm LED lamps (EN 12352 L2H, 1500 cd) on a fixed surface mount.

EN 12352  
Class L2H

BEK 393/2025  
Compliant (DK)

RS485  
Canbus control

OPTICAL FEATURES

Light source

15 x amber LED lamps, Ø140 mm light opening (Ø150 mm housing)

EN 12352 class

L2H

Luminous intensity

1500 cd per lamp

Display modes

Cross, arrow left, arrow right, corner lamps

Flash cycle

1.5 s period, 0.6 s lit

Dimming

Photosensor-driven, 5-level automatic

ELECTRICAL FEATURES

Supply voltage

12 V (24 V via external converter kit)

Lamp current

0.42 A per lamp

Average power consumption

approx. 1.5 A / 18 W (daylight, 12 V, max. 9 lamps lit, lamps only)

Control

RS485 canbus, back-lit operator panel

Remote control

Prepared for radio remote (2x4 or 3x5 radio transmitter, sold separately)

MECHANICAL FEATURES

Panel size

800 x 800 mm

Mounting

Fixed surface mounting on vehicle body, tailgate, roof rack or hoop frame

Housing

Matte-black aluminium with stainless-steel frame

Weight

approx. 20 kg

