

Avatar 80P

Temporary Redirective Crash Cushion, Parallel (CE-certified per EN 1317-3)

TECHNICAL FEATURES

Description

Self-standing redirective crash cushion designed for road construction sites and extraordinary maintenance. Minimum anchorage requirements, pre-assembled, entirely steel, fully repairable. ASI B, Z1, D1 performance.

CE
Certified

EN 1317-3
Tested

Parallel
Compact
profile

**Self-
Standing**
Min.
anchorage

Repairable
Reusable

Z1 / D1
ASI B

PRODUCT FEATURES

Category	Crash Cushions, Redirective (Temporary / Work-Zone)
Product type	Parallel redirective crash cushion, temporary
Application	Road construction sites, extraordinary maintenance
Anchoring	20 anchors, asphalt or concrete (Ø 24 mm, depth 165 mm)
Installation options	Threaded socket frame or chemical anchors
Material	Steel (entirely)
Repairability	Fully repairable after impact
Delivery condition	Pre-assembled, ready for installation

APPROVALS & TESTING

Test standard	EN 1317-3
Certification	CE Certified
Performance	ASI B, Z1, D1 (redirective)

DIMENSIONS

Component	Value
Length	3540 mm
Front width	580 mm
Rear width	580 mm
Height	600 mm
Number of holes	20
Hole diameter	24 mm
Hole depth	165 mm

The Avatar 80P is the parallel-profile member of the Avatar family, providing EN 1317-3 redirective performance for temporary work-zone installations.

