

ProGuard Flood Light

Flood light for the ProGuard Lighting pole · ProGuard Lighting

TECHNICAL FEATURES

Description

Flood light for the ProGuard Lighting system, mounted on the lighting pole with the floodlight pole bracket (Art. 90098). Together with the 4.5 m lighting pole and the CB pole bracket it provides rapidly deployable lighting for the work zone and the surrounding area, mounted directly on ProGuard CB barriers.

6.5 kg
Weight

Pole mount
Via bracket 90098

For CB
ProGuard Lighting

Rapid
Deployment

GENERAL

Product type	Flood light for mobile work zone lighting
Application	Work zone and surrounding area lighting on ProGuard CB barriers
System components	Lighting Pole Art. 90096 · Floodlight Pole Bracket Art. 90098 · Lighting Pole Bracket Art. 10440

DIMENSIONS & WEIGHT

Length	230 mm
Width	408 mm
Height	354 mm
Weight	6.5 kg

MOUNTING

Pole interface	Floodlight pole bracket on the 4.5 m lighting pole
Barrier interface	Lighting pole in the ProGuard CB fork pocket via the lighting pole bracket



ProGuard Lighting integrates directly with ProGuard CB and provides rapidly deployable lighting for the work zone and the surrounding area. The pole fixes in the barrier's fork pocket with the lighting pole bracket (Art. 10440) and carries the flood light on the floodlight pole bracket (Art. 90098).