

ProGuard Lighting Pole

4.5 m pole for the ProGuard CB fork pocket · ProGuard Lighting

TECHNICAL FEATURES

Description

Lighting pole for ProGuard CB barriers. Fixes in the barrier's fork pocket with the lighting pole bracket, giving a rigid mount that withstands high wind loads, to light the area outside the site enclosure or the work zone inside the closure.

4.5 m

Pole length

Ø 108 mm

Pole diameter

11 kg

Weight

For CB

Fork-pocket mount

GENERAL

Product type	Lighting pole for mobile work zone lighting
Application	Area lighting outside the enclosure or work lighting inside the closure
System components	Lighting Pole Bracket Art. 10440 (200 x 200 x 1200 mm, 5.2 kg) · Flood Light Art. 90097 · Floodlight Pole Bracket Art. 90098

DIMENSIONS & WEIGHT

Length	4.5 m
Diameter	Ø 108 mm
Weight	11 kg

MOUNTING

Barrier interface	ProGuard CB fork pocket via the lighting pole bracket
Stability	Rigid mount that withstands high wind loads



ProGuard Lighting integrates directly with ProGuard CB and provides rapidly deployable lighting for the work zone and the surrounding area. The pole fixes in the barrier's fork pocket with the lighting pole bracket (Art. 10440) and carries the flood light on the floodlight pole bracket (Art. 90098).