



viasis LITE PLUS

Radar speed display · 2-digit multicolour LED · text and symbol display

TECHNICAL FEATURES

LED
editor

2-digit
LED display

Smile
function

Light
housing

Multi-LED
colour change

Data
storage

Description

Large and long-distance visible radar speed display in a lightweight housing. The multicolour LEDs offer display options in 8 different colours. The lower multicolour text and symbol display shows single and double-line texts as well as symbols. With data storage, smile function, Bluetooth communication, rotary switch and USB interface.

DISPLAY FEATURES

Display type	2-digit high performance LED display, multicolour, with text and symbol display underneath
Digit height	32,5 cm / 12,8"
LED colours	8 colours can be set
Text and symbol display	Multicolour (RGB LED), single and double-line texts and symbols; 16 preset pages, fully redesignable with the LED editor
Brightness	Automatic brightness control
Protection mask	Specially designed, for excellent visibility even in strong sunlight

MEASUREMENT & DATA FEATURES

Measurement direction	Bidirectional measurement, adjustable
Measuring range	1-255 km/h
Display range	1-99 km/h
Smile function	Smile / neutral / frown feedback depending on driven speed
LED colour change	If speed limit is exceeded (8 colours can be set)
Adjustable parameters	Min. and max. speed, LED colour change, flashing display and smile function
Parameter sets	5 parameter sets, depending on time and day
Data storage	Ring buffer, exact to the second
Clock	Timer with automatic daylight saving time

ELECTRICAL FEATURES & INTERFACES

Battery level indicator	Integrated
Communication	Bluetooth communication with viagraph 5 (PC) or app (Android / iOS)
USB interface	Data download, parameter changes or firmware update
Manual parameter setting	Rotary switch
Remote data transfer	4G modem + GPS + SIM card + viacloud access (optional)
Power supply options	12 V / 22 Ah battery (accessory) · optionally available with 230 V and / or solar connection

MECHANICAL FEATURES

Dimensions (W x H x D)	60,5 x 87 x 15 cm / 23,8" x 34,2" x 5,9"
Housing	Impact-resistant and UV-stable lightweight housing (ABS / PMMA)
Mounting options	Lockable mounting kit for poles ø 40 - 160 mm · tripod · two-part pole with ground sleeve (accessories)



Write your own texts and design graphics with the LED editor.

