

TTMA-200 Trailer Finland + Folding Board

FI reflex panels · Prepared for LP 15+2 · Level 2

TECHNICAL FEATURES

DESCRIPTION
The NTS TTMA-200 is a trailer truck mounted attenuator for road works and mobile work zones. It couples to the towing vehicle's standard draw eye and delivers MASH 2016 TL-3 impact protection without a dedicated TMA vehicle. Impact energy is absorbed by a patented tube bursting system in which the deformed elements stay attached to the trailer. Supplied without the light arrow control unit and lamp set, which are ordered separately.

SCOPE OF DELIVERY	
Trailer	TTMA-200 Finland
Coupling	50 mm draw eye, hitch extension
Trailer equipment	Fenders, trailer light set 24 V
Warning board frame	Folding, electric lift LA36, arrow setting motor
Reflex panels	Panel set Finland, aluminium with reflex foil
Light arrow control unit	Not included, ordered separately
Lamp set	Not included, ordered separately

LIGHT ARROW PREPARATION	
Prepared for firmware	LP 15+2 (Finland)
Lamp positions on the board	15x L8H Ø200 mm, 2x L9H Ø300 mm
Control unit	Not included, ordered separately
Lamp set	Not included, ordered separately
Board movement	Electric lift LA36, electric arrow setting motor

TECHNICAL SPECIFICATIONS	
Dimensions (W x H x L)	244 x 79 x 750 cm
Weight, without board	720 kg
Axle rating	750 kg
Tyres	185R14C at 350 kPa
Draw eye height	50 to 80 cm
Hitch extensions	S, M, L and XL, to 122 cm
Tow coupling, min. D-value	8.125 kN
Minimum support vehicle	4,536 kg GVW
Surface treatment	Hot-dip galvanised, EN ISO 1461
Electrical system	24 V

APPROVALS	
Crash test standard	AASHTO MASH 2016 Test Level 3
Tests passed	3-50, 3-51, 3-52, 3-53 and 3-54, all at approx. 100 km/h
FHWA eligibility letter	CC-152
Swedish Transport Administration	Trafikverket TRV 2020/78913
Registration	National requirement, quoted separately
Inspection, Finland	Inspection (katsastus) and licence plate quoted separately



The illustration shows a complete system. The light arrow control unit and the lamp set are not included in this configuration.