

TTMA-200 System Sweden without lamps

Folding board · E13 speed sign · LP 25+2 · 3x5 remote · Level 3

TECHNICAL FEATURES

DESCRIPTION

The NTS TTMA-200 is a trailer truck mounted attenuator for road works and mobile work zones. It couples to the towing vehicle's standard draw eye and delivers MASH 2016 TL-3 impact protection without a dedicated TMA vehicle. Impact energy is absorbed by a patented tube bursting system in which the deformed elements stay attached to the trailer. Supplied without the lamp set, which is ordered separately.

SCOPE OF DELIVERY

Trailer	TTMA-200 Sweden, MASH 2016 TL-3
Coupling	VBG 57.5 mm draw eye, hitch extension S-VBG
Trailer equipment	Fenders, assembled and ready for the warning board
Warning board frame	Folding, electric lift LA36, arrow setting motor
Board panels	Sweden metal parts set, alu sheet RAL 7042, speed sign bracket kit
Speed sign	E13, 60 x 60 cm, 30 to 70 km/h symbols
Light arrow control unit	NTS LP28 with 3x5 push button radio remote, without GSM
Lamp set	Not included, ordered separately

LIGHT ARROW SYSTEM

Firmware	LP 25+2 SE
Lamp positions on the board	25x L8H Ø200 mm, 2x L9H Ø300 mm
Lamp set	Not included, ordered separately
Remote control	3x5 push button radio remote
Board movement	Electric lift LA36, electric arrow setting motor
Speed sign	E13 60 x 60 cm, 30 to 70 km/h

TECHNICAL SPECIFICATIONS

Dimensions (W x H x L)	244 x 79 x 750 cm
Weight, without board	720 kg
Axle rating	750 kg
Tyres	185R14C at 350 kPa
Draw eye height	50 to 80 cm
Hitch extensions	S, M, L and XL, to 122 cm
Tow coupling, min. D-value	8.125 kN
Minimum support vehicle	4,536 kg GVW
Surface treatment	Hot-dip galvanised, EN ISO 1461
Electrical system	24 V

APPROVALS

Crash test standard	AASHTO MASH 2016 Test Level 3
Tests passed	3-50, 3-51, 3-52, 3-53 and 3-54, all at approx. 100 km/h
FHWA eligibility letter	CC-152
Swedish Transport Administration	Trafikverket TRV 2020/78913
Registration	National requirement, quoted separately
National requirement, Sweden	Towing vehicle minimum 8,600 kg GVW excluding the TMA



The illustration shows a complete system. The lamp set is not included in this configuration.