

# Deltaline SC · profiled · yellow

Typ II · P7 — Profiled Temporary Road Marking Tape (BASt-approved per ZTV M 13)

## TECHNICAL FEATURES

Description
Profiled yellow temporary road marking film (Typ II per ZTV M 13) with a raised stud-pattern surface that delivers enhanced grip, wet-night reflectivity, and strong acoustic and haptic feedback when driven over. Recommended for roadwork zones on open-porous asphalt (OPA) and for the highest ZTV M 13 traffic class (P7). BASt-approved (Prüfnummer 2022 1VF 05.16) and tested per DIN EN 13197 / DIN EN 1436.

<b>BASt</b> Approved	<b>ZTV M 13</b> Compliant	<b>EN 1436</b> Tested
<b>Typ II</b> P7 · profiled		

## PRODUCT FEATURES

Category	Road Marking Tapes — Temporary Tapes
Marking type	Typ II — profiled marking film with raised surface structure
Surface	Profiled (raised stud pattern)
Application	Temporary markings (roadwork zones, OPA, heavy-traffic sites)
Colour	Yellow
Primer	NTS Primer P-20
Application method	Roll-on (aufgewalzt)

## APPROVALS & STANDARDS

BASt-Approval Number	2022 1VF 05.16
Issuing authority	Bundesanstalt für Straßenwesen (BASt)
Reference standards	ZTV M 13 · TP M 18 · TL M 06
Test standards	DIN EN 13197 · DIN EN 1436
Conformity statement	Meets minimum requirements of ZTV M 13 for use in Germany

## PERFORMANCE — DIN EN 1436

Property	New (Neuzustand)	Used (Gebrauchszustand)
Grip (Griffigkeit)	S 3	S 2
Night-time visibility — dry (Nachtsichtbarkeit, trocken)	R 5	R 5
Night-time visibility — wet (Nachtsichtbarkeit, feucht)	RW 6	RW 5
Daytime visibility (Tagessichtbarkeit)	Q 3	Q 3
Colour (Farbbereich)	Y 2	Y 2

## ADDITIONAL ZTV M 13 REQUIREMENTS

Traffic class (Verkehrsklasse)	P7	
Colour location (Anforderungen Farbort)		Compliant (erfüllt)
Wear resistance — 90% residual surface		Compliant (erfüllt)

The product satisfies the wear resistance regulation, which stipulates that at least 90% of the tape must remain intact as long as it is on the road.

